

2001 1600
 FILED
 RECORDERS OFFICE
 JONES COUNTY IOWA
 01 MAY 15 AM 10:16
 MARIE KRUTZFIELD
 RECORDER No Fee

J.D. TJEPKES, LS. JONES COUNTY ENGINEER'S OFFICE, 19501 HWY. 64, ANAMOSA, IOWA, 52205 (319)462-3785

UNITED STATES PUBLIC LAND SURVEY CORNER CERTIFICATE

LAND SURVEY MONUMENTS SITUATED IN SECTION 1, TOWNSHIP 83
 NORTH, RANGE 2 WEST OF THE 5TH P.M., JONES COUNTY, IOWA

CORNERS TO BE INDEXED

CORNER	SECTION	TOWNSHIP	RANGE
EAST 1/4	1	83N	2W

OFFICE FILE NO. 83201o_041201

NOTE: ALL SLOPE DISTANCES

FOUND 5/8" IRON PIN 6" BELOW SURFACE IN C.L. ROAD. PER RECORDED TIES E-1/4 COR. 1-83-2

PLASTIC SURVEY DISKS IN FENCE POSTS

PLASTIC SURVEY DISK IN FENCE POST

PLASTIC SURVEY DISK IN POWER POLE

COUNTY FIELD BOOK NO. 359

70TH AVE.

PREVIOUSLY RECORDED IN BOOK 334, PAGE 48

MONUMENT DESCRIPTION AND HOW ESTABLISHED FOUND 5/8" REBAR IN CENTERLINE OF ROAD, 6" BELOW SURFACE PER RECORDED TIES. SET NEW REFERENCE POINTS AND TIED OUT AS INDICATED. EAST QUARTER CORNER SEC. 1, TOWNSHIP 83 NORTH, RANGE 2 WEST, JONES COUNTY, IOWA

CORNERS TO BE INDEXED

CORNER	SECTION	TOWNSHIP	RANGE
NORTHEAST	1	83N	R2W

OFFICE FILE NO. 83201e_041201

PLASTIC SURVEY DISK IN FENCE POSTS

70TH STREET

70TH AVE.

PLASTIC SURVEY DISK IN POWER POLE

FOUND 5/8" REBAR NORTH AND EAST OF ROAD. NE. COR. SEC. 1, T83N, R2W, JONES COUNTY, IOWA

COUNTY FIELD BOOK NO. 359

NOTE: ALL SLOPE DISTANCES

PREVIOUSLY RECORDED IN BOOK 334, PAGE 48

MONUMENT DESCRIPTION AND HOW ESTABLISHED FOUND 5/8" IRON PIN NORTH AND WEST OF ROAD PER RECORDED TIES SET NEW REFERENCE POINTS AND TIED OUT AS INDICATED. NORTHEAST CORNER OF SECTION 1, TOWNSHIP 83 NORTH, RANGE 2 WEST, JONES COUNTY, IOWA

CORNERS TO BE INDEXED

CORNER	SECTION	TOWNSHIP	RANGE
N-1/4	1	83N	2W

OFFICE FILE NO. 83201c_041201

SET SURVEY SIGN IN FENCE LINE

PLASTIC SURVEY DISK IN POWER POLE

OVERHEAD POWER LINE

SET 5/8"X48" REBAR WITH CAP LS 14807 & MAGNET N-1/4, 1-83-2

PREVIOUSLY RECORDED IN BOOK N/A, PAGE N/A

MONUMENT DESCRIPTION AND HOW ESTABLISHED SET 5/8"X48" REBAR WITH CAP LS 14807 AT PROPORTIONATE DISTANCE BETWEEN NORTHEAST AND NORTHWEST SECTION CORNERS. SET REFERENCE POINTS AND TIED OUT AS INDICATED. N-1/4, SEC. 1, T83N, R2W, JONES COUNTY, IA.

CORNERS TO BE INDEXED

CORNER	SECTION	TOWNSHIP	RANGE
CENTER	1	83N	2W

OFFICE FILE NO. 83201m_041701

N-1/4 SECTION 1

W-1/4 SECTION 1

E-1/4 SECTION 1

S-1/4 SECTION 1

SET 5/8"X48" REBAR 1.5' BELOW SURFACE IN OPEN FIELD, CENTER SEC. 1


PREVIOUSLY RECORDED IN BOOK N/A, PAGE N/A

MONUMENT DESCRIPTION AND HOW ESTABLISHED SET 5/8"X48" REBAR WITH CAP LS 14807 1.5' BELOW SURFACE. MONUMENT SET AT INTERSECTION OF CROSSED LINES FROM OPPOSITE QUARTER CORNERS. CENTER SECTION 1, TOWNSHIP 83 NORTH, RANGE 2 WEST, JONES COUNTY, IOWA

I hereby declare that this plat, survey or report was made by me or under my direct personal supervision and that I am a duly registered Land Surveyor under the laws of the State of Iowa.

Signed: *Joseph D. Tjepkes* 5-14-01

Joseph D. Tjepkes L.S. Iowa Reg. No. 14807
 My Registration Renewal Date is December 31, 2002



J.D. TJEPKES LS 14807
 JONES COUNTY
 ENGINEER'S OFFICE

19501 HWY. 64,
 ANAMOSA, IOWA,
 52205 (319)462-3785